





DC 1000 V Ø 10 x 38 mm




50 215 26



50 216 26



50 217 26



50 218 26

Verpackungseinheit / Packing unit: 10 Stück / 10 pieces

Betriebsklasse / Class gPV gR	IEC 60 269-6 UL 248-13
---	-----------------------------------

Bemessungs- spannung Rated Voltage	Artikel Nr. Article No	Größe Size	Bemessungsstrom Rated Current	max Anzugsdrehmoment max. Tightening Torque
V			A	Nm
DC 1000	50 215 26	Ø 10 x 38 mm	1-20	-
	50 216 26	Ø 10 x 38 mm	1-20	-
	50 217 26	Ø 10 x 38 mm	1-20	3,5
	50 218 26	Ø 10 x 38 mm	1-20	-

Bemessungsausschaltvermögen / Rated breaking capacity **30 kA DC 1000 V**
L/R ≈ 2 ms

Bemessungs- strom Rated Current	Artikel Nr. Article No.				Gewicht Weight	Bemessungsspannung Rated Voltage		Schmelz- integral Pre-Arcing I ² t-Value	Ausschalt- integral Total i ² t-value @ DC 1000 V L/R ≈ 2ms	Leistungs- abgabe ¹ Power Loss ¹
		mit Einlötpins, Ms verzinkt with soldering contacts, brass tin plated	mit Anschraub- laschen with bolted contacts	für Kabel- montage for cable connections		IEC 60 269-6	UL 248-13			
A					kg / 1	V	V	A ² s	A ² s	W
1	50 215 26.1	50 216 26.1	50 217 26.1	50 218 26.1	0,01	DC 1000	DC 1000	0,33	0,5	0,8
1,6	50 215 26.1.6	50 216 26.1.6	50 217 26.1.6	50 218 26.1.6	0,01	DC 1000	DC 1000	1,5	2	1,1
2	50 215 26.2	50 216 26.2	50 217 26.2	50 218 26.2	0,01	DC 1000	DC 1000	3	4	1,2
3	50 215 26.3	50 216 26.3	50 217 26.3	50 218 26.3	0,01	DC 1000	DC 1000	12	17	1,6
3,5 ²	50 215 26.3.5 ²	50 216 26.3.5 ²	50 217 26.3.5 ²	50 218 26.3.5 ²	0,01	DC 1000		8	11	1,5
4	50 215 26.4	50 216 26.4	50 217 26.4	50 218 26.4	0,01	DC 1000	DC 1000	10	14	1,8
5	50 215 26.5	50 216 26.5	50 217 26.5	50 218 26.5	0,01	DC 1000	DC 1000	20	28	2,0
6	50 215 26.6	50 216 26.6	50 217 26.6	50 218 26.6	0,01	DC 1000	DC 1000	32	45	2,5
8	50 215 26.8	50 216 26.8	50 217 26.8	50 218 26.8	0,01	DC 1000	DC 1000	5	50	1,6
10	50 215 26.10	50 216 26.10	50 217 26.10	50 218 26.10	0,01	DC 1000	DC 1000	7	68	2,0
12	50 215 26.12	50 216 26.12	50 217 26.12	50 218 26.12	0,01	DC 1000	DC 1000	10	100	2,4
15	50 215 26.15	50 216 26.15	50 217 26.15	50 218 26.15	0,01	DC 1000	DC 1000	30	290	1,9
16	50 215 26.16	50 216 26.16	50 217 26.16	50 218 26.16	0,01	DC 1000	DC 1000	30	290	2,1
20	50 215 26.20	50 216 26.20	50 217 26.20	50 218 26.20	0,01	DC 1000	DC 1000	52	500	2,5

Applikationskoeffizienten / Application coefficients (Weiterführende Informationen [hier zum Download](#) / for more information [download here](#))

a	A2	B1 max.	B2	Cf3
130	0,9	1,25	0,5	0,8

DC 1000 V

Ø 10 x 38 mm

usE180276

Zeit/Strom-
Kennlinien
Time-current
characteristics

